

Flexo Print

TL 140W/03

Flexo print TL lamps emit almost all of their light (99.9%) in the useful UVA and visible blue wavebands - between 350 and 400 nm - and have peak intensity at 370 nm (except for the /03 version). This makes them ideal for flexo printing equipment and photopolymerization processes. In addition, the 'R' lamps in the family have an internal 200degree reflector to further optimize the lamp's overall efficiency.

Product data

• General Characteristics

Cap-Base G13 Bulb Main Application Reprography 3000 hr Useful Life Life to 50% failures 5000 hr

EM

• Light Technical Characteristics

Color Code	03
Color Designation	Super Actinic
(text)	
Chromaticity Coor-	175 -
dinate X	
Chromaticity Coor-	45 -
dinate Y	
Depreciation 500	20 %
hours	
Depreciation 1000	30 %
hours	
Depreciation 2000	40 %
hours	

• Electrical Characteristics

Lamp Wattage	140 W		
Lamp Wattage Tech-	142 W		
nical			
Lamp Voltage	118 V		
Lamp Current	1.46 A		
Mains Voltage Stable	30.4 W		
Operation			

• UV-related Characteristics

UV-A Radiation 1.00 W 100hr (IEC)

• Product Dimensions

Base Face to Base 1500 (max) mm Face A Insertion Length B 1504.7 (min), 1507.1 (max) mm 1514.2 (max) mm Overall Length C Diameter D 40.5 (max) mm

> 928012700303 928012700303

• Product Data Order code

Full product code


Full product name TL 140W/03 Order product name TL 140W/03 Pieces per pack Packing configuration 25 Packs per outerbox 25 8711500720948 Bar code on pack -EAN1 8711500720955 Bar code on outerbox - EAN3 928012700303 Logistic code(s) -12NC Net weight per piece 331.000 gr



Dimensional drawing

TL G13


Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TL 140W/03	1500	1504.7	1507.1	1514.2	40.5






G13

Photometric data







Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.