



Halogen High Voltage SE (Film/Studio)

6994Y 2000W G22 230V 1CT

The high, constant output and consistent color temperature of these single ended halogen lamps ensure attractive, accurately exposed pictures for both film and video. Furthermore, these lamps incorporate the highly innovative P3 technology, developed by Philips. This allows the lamps to be used at higher temperatures, which extends overall lifetime and consistency of their high-quality light output. P3 technology also allows the lamp to be used in any burning position and enables more compact designs of fixtures. In addition, the very wide choice of dimensions and power ratings opens new levels of creative freedom for the luminaire designer.

Product data

• General Characteristics

Philips Code	6994Y
ANSI Code	-
LIF Code	CP/75 (CP/55)
System Description	-
Cap-Base	G22
Bulb Finish	Clear
Filament Shape	Bi-Plane
Operating Position	s90
Main Application	Entertainment
Life to 50% failures	480 hr

• Light Technical Characteristics

Color Temperature	3200 K
Technical	
Luminous Flux Lamp	50000 Lm

• Electrical Characteristics

Lamp Wattage	2000 W
Voltage	230 V
Dimmable	Yes
Rapid Acting HBC	16 V
Fuse	

• Luminaire Design Requirements

Pinch Temperature	400 (max) C
-------------------	-------------

• Product Dimensions


Overall Length C	160 (max) mm
Diameter D	40 (max) mm
Pin Length K	24.89 (min), 26.54 (max) mm
Light Center Length L	75 mm
Pin Diameter P	6.30 (min), 6.40 (max) mm
Pin Distance R	22.22 mm
Filament Dimensions (WxH) [mm]	20x20
Filament Height H	18.5 mm
Filament Length W	17 mm

• Product Data

Order code	923894742948
Full product code	923894742948
Full product name	6994Y 2000W G22 230V 1CT
Order product name	6994Y 2000W G22 230V 1CT/10
Pieces per pack	1
Packing configuration	10
Packs per outerbox	10
Bar code on pack - EAN1	8711500506573
Bar code on outerbox - EAN3	8711500507600
Logistic code(s) - 12NC	923894742948
Net weight per piece	110.000 gr

Dimensional drawing

Dimensional drawing



G22

Product	C (Max)	D (Max)	H (Norm)	K (Min)	K (Norm)	K (Max)	L (Min)	L (Norm)	L (Max)	P (Min)	P (Norm)	P (Max)	R (Min)	R (Norm)	R (Max)	W (Norm)
6994Y 2000W G22 230V	160	40	18.5	24.89	-	26.54	-	75	-	6.30	-	6.40	-	22.22	-	17

