

Hi-Brite

7015TXO 750W GX9.5 100V 1CT

The compact, shock-resistant design of the Hi-Brite lamp series makes it easy to handle and ideal for moving head systems. Also, the compact filament ensures a high beam intensity, which can be used to reduce energy consumption: for example, 1200W can now be used instead of 2500W. In addition, the highly innovative P3 technology, developed by Philips, allows the lamp to be used at higher temperatures in any burning position, which further extends lamp lifetime, reduces lamp replacement costs and ensures consistency of high-quality light output.

Product data

• General Characteristics

Philips Code 7015TXO
ANSI Code System Description P3 Technology
Cap-Base GX9.5
Bulb Finish Clear
Filament Shape Bi-Plane
Operating Position any
Main Application Entertainment

Life to 50% failures 300 hr

• Light Technical Characteristics

Color Temperature 3200 K

Technical

Luminous Flux Lamp 20250 Lm

• Electrical Characteristics

Lamp Wattage 750 W Voltage 100 V Dimmable Yes

• Luminaire Design Requirements

Pinch Temperature 500 (max) C

Dimensional drawing

• Product Dimensions

Overall Length C 104 (max) mm
Diameter D 19 (max) mm
Light Center Length 55 mm

.....

Filament Dimensions (WxH) [mm]

Filament Height H 8.5 mm Filament Length W 9.5 mm

• Product Data

Order code 924574530928 Full product code 924574530928

Full product name 7015TXO 750W GX9.5 100V 1CT

8711500505583

Order product name 7015TXO 750W GX9.5 100V

Pieces per pack 1
Packing configuration 10
Packs per outerbox 10

Bar code on pack - 8711500505576

EAN1 Bar code on

outerbox - EAN3


Logistic code(s) - 924574530928

12NC

Net weight per piece 0.037 kg




Dimensional drawing



7015TXO 750W GX9.5 100V 1CT

Product	C (Max)	D (Max)	H (Norm)	L (Norm)	W (Norm)
7015TXO 750W GX9.5 100V	104	19	8.5	55	9.5





Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.