



Product Description

Video/Photo/ENG SE

Single-ended mains-voltage halogen lamps

Benefits

- High, constant light output and high colour temperature form the basis for making attractive, accurately exposed pictures


Application

- Portable film and video lights
- Reproduction cameras
- Modelling lights for flash equipment
- ENG (Electronic News Gathering)

Related products




G6.35




GX6.35

Dimensional drawing



G6.35

Product	C (Max)	D (Max)	H (Norm)	K (Min)	K (Norm)	K (Max)	L (Norm)	P (Min)	P (Norm)	P (Max)	R (Min)	R (Norm)	R (Max)	W (Norm)
PF810 650W G6.35 230V	67	18	2.8	7.5	-	-	41	0.95	1	1.05	6.1	6.35	6.6	3.5
PF810 650W G6.35 240V	67	18	2.8	7.5	-	-	41	0.95	1	1.05	6.1	6.35	6.6	3.5



GX6.35

Product	C (Max)	D (Max)	H (Norm)	K (Min)	K (Norm)	K (Max)	L (Norm)	P (Min)	P (Norm)	P (Max)	R (Min)	R (Norm)	R (Max)	W (Norm)
VL150 150W GX6.35 230V	54	18	6	6.5	7	7.5	30	0.95	1	1.05	6.1	6.35	6.6	6
VL150 150W GX6.35 240V	54	18	6	6.5	7	7.5	30	0.95	1	1.05	6.1	6.35	6.6	6
VL300 300W GX6.35 120V	56	18	9	6.5	7	7.5	31.5	0.95	1	1.05	6.1	6.35	6.6	6
VL300 300W GX6.35 230V	56	18	9	6.5	7	7.5	31.5	0.95	1	1.05	6.1	6.35	6.6	6
VL300 300W GX6.35 240V	56	18	9	6.5	7	7.5	31.5	0.95	1	1.05	6.1	6.35	6.6	6
PF808 300W GX6.35 230V	56	18	9	6.5	7	7.5	31.5	0.95	1	1.05	6.1	6.35	6.6	6

Compare table

Order code	Full product name	ANSI Code	Bulb Finish	Cap-Base	Dimmable	Filament Shape	Lamp Wattage	LIF Code	Life to 50% failures	Luminous Flux Lamp	Main Application
923875143258	PF810 650W G6.35 230V 1CT	-	Clear	G6.35	Yes	Coiled Coil	650	P1/14	15	21100	Video/Photo/Eng
923875145758	PF810 650W G6.35 240V 1CT	-	Clear	G6.35	Yes	Coiled Coil	650	P1/14	15	21100	Video/Photo/Eng
923949343258	VL150 150W GX6.35 230V 1CT	-	Clear	GX6.35	Yes	M	150	-	20	3750	Video/Photo/Eng
923949345758	VL150 150W GX6.35 240V 1CT	-	Clear	GX6.35	Yes	M	150	-	20	3750	Video/Photo/Eng
923949436358	VL300 300W GX6.35 120V 1CT	-	Clear	GX6.35	Yes	M	300	-	20	8700	Video/Photo/Eng
923949443258	VL300 300W GX6.35 230V 1CT	-	Clear	GX6.35	Yes	M	300	-	20	8550	Video/Photo/Eng
923949445758	VL300 300W GX6.35 240V 1CT	-	Clear	GX6.35	Yes	M	300	-	20	8550	Video/Photo/Eng
924000743258	PF808 300W GX6.35 230V 1CT	-	Clear	GX6.35	Yes	M	300	-	15	8550	Video/Photo/Eng

Compare table

Order code	Full product name	Operating Position	Philips Code	Voltage	Rapid Acting HBC Fuse
923875143258	PF810 650W G6.35 230V 1CT	any	PF810	230	4
923875145758	PF810 650W G6.35 240V 1CT	any	PF810	240	4
923949343258	VL150 150W GX6.35 230V 1CT	any	VL150	230	2
923949345758	VL150 150W GX6.35 240V 1CT	any	VL150	240	4
923949436358	VL300 300W GX6.35 120V 1CT	any	VL300	120	4
923949443258	VL300 300W GX6.35 230V 1CT	any	VL300	230	2
923949445758	VL300 300W GX6.35 240V 1CT	any	VL300	240	2
924000743258	PF808 300W GX6.35 230V 1CT	any	PF808	230	2



© 2011 Koninklijke Philips Electronics N.V.
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com/lighting

2011, February 24
data subject to change