

PAR56 and PAR64

PAR56 300W 240V WFL

These self-contained spotlights are ideal for intensifying the visual experience in all kinds of clubs, that is because their accurate beam control picks out even the smallest of details even over long distances. This beam control makes the PAR 56 and PAR 64 excellent for long-range light projections. In addition, the universal burning feature provides complete flexibility of luminaires angle and position, while the front glass of the PAR56 provides thermal and physical protection. The result? Complete creative freedom to achieve the desired effect. Immediate re-strike also ensures instant resumption of entertainment after any power interruption.

Product data

• General Characteristics

ANSI Code LIF Code Cap-Base GX16d
Cap-Base Information Bulb -

Operating Position any

Main Application Flood and Ambient Lighting

Average Lifetime 2000 hr Life to 50% failures 2000 (min) hr

• Light Technical Characteristics

Beam Description Wide Flood [Wide Flood]

Beam Angle 40 D Beam Angle Tech-40 D

nical

Luminous Intensity 10000 (max) cd

Color Temperature 2000 K

• Electrical Characteristics

Lamp Wattage 300 W Voltage 240 V

• Environmental Characteristics

Energy Efficiency Label (EEL)

Dimensional drawing

• Product Dimensions

Overall Length C 127 (max) mm Diameter D 178 (max) mm

• Product Data

Order code 924783745504
Full product code 924783745504
Full product name PAR56 300W 240V WFL
Order product name Par56 WFL 300W 240V GX16d.

8711500441973

924783745504

Pieces per pack 1
Packing configuration 6
Packs per outerbox 6

Bar code on pack - 8711500441966

EAN1 Bar code on outerbox - EAN3


Logistic code(s) -

12NC

Net weight per piece 0.542 kg



Dimensional drawing



PAR56 300W 240V WFL

Product	C (Max)	D (Max)
PAR56 300W 240V WFL	127	178



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.