



EN 60598-1 230V / 50Hz IP 66 IR3   RoHS



Domeniul de utilizare: Dirijarea primului vehicul aflat la o intersecție

Descriere:

Corp: Din PC pe care se montează în exterior cele două racorduri de fixare din PC

Ușa: Din PC pe care se suprainjectează dispersorul din PC transparent (roșu, galben, verde) prevăzut cu parasolar

În interiorul corpului se fixează module cu LED

Montaj: Pe stâlp la o înălțime de 1,3 m, cu ajutorul racordurilor prevăzute cu găuri pentru șuruburi M6 și canal pentru colier

Diametrul suprafeței luminoase: 80mm pentru fiecare compartiment

Conectarea: La rețeaua electrică se realizează prin racordul superior

La cerere se poate livra cu două module (roșu și verde)

Sursa: LED-uri verzi, roșii, galbene,

Standard: SR EN 60598-1, SR EN - 12368

Application: Guiding at the red light the first car waiting

Description:

Body: Made of PC with two PC brackets

Door: Made of PC, on which is over - injected the clear PC diffuser (red, yellow, green) fitted with sun protector

LED modules are fitted on the inside of the body

Mounting: On poles by means of the joint-brackets with holes for M6 screws and collar channel, at a height of approx.1,3 m

Diffuser diameter: 80 mm for each lamp

Connection: To the electrical network connection supply by means of the superior joint-brackets

On request may be delivered with two LED modules (red and green)

Source: Red, green, yellow LED,

Standard: SR EN 60598-1, SR EN- 12368

Tip/Type	Cod produs/ Product code	Corp-ușă-cozoroc/ body-door-cap	Mască/ Masc	Culoare/ colour	Masa/ Weight [kg]	Lampa/ Lamp
3x1W	75412062	PC	fără/without		1.00	LED 
2x1W	75414000	PC	fără/without		0.70	

