



EN 60598-1	230V / 50Hz	IP 20	IK 06		960°C	CE	RoHS	250W
------------	-------------	-------	-------	--	-------	----	------	------

Domeniul de utilizare:
Iluminatul general de interior pentru spații întinse

Descriere:

Corp: Din aliaj de aluminiu turnat sub presiune

Inel distanțier: Din tablă perforată, acoperită cu pulbere

Reflector: Din tablă de aluminiu aluminizat, cu coeficient de reflexie > 0.85

Cutie aparataj: Din aliaj de aluminiu turnat sub presiune

Variante:

- cu grătar de protecție (G) fixat pe reflector prin intermediul unui colier
- cu sticlă de protecție termorezistentă, securizată, fixată pe reflector prin intermediul unui colier

Montaj:

Sursa : Halogenuri metalice de 250W (PDHM), mercur (PDVM)

Dulie: E40

Standard: SR EN 60598-1

Application:
General lighting of large indoor areas

Description:

Body: Diecast aluminum alloy

Distance ring: Made of punched sheet, painted with powder

Reflector: Aluminum sheet reflector, aluminized, with a reflection factor > 0.85

Gear box: Made of diecast aluminum alloy

Variants:



- with protection grid (G) fixed with a collar on the reflector
- with thermoresistant, tempered protective glass fixed with a collar on the reflector

Mounting:

Source: Metallic halides 250W (PDHM), mercury (PDVM)

Socket: E40

Standard: SR EN 60598-1



Grătar protecție/protective grid
Cod / Code: 30171004

PDHM 09

Tip/Type	Cod produs/ Product code	Factor de putere/ Power factor	Dimensiuni/Dimensions [mm]			Accesorii/ Accessories	Masa/ Weight [kg]	Lampa/ Lamp
			φ	H	φ I			
1x250W halogenură metalică/ metal halide	30171009	min. 0.92	460	450	450	sticlă securizată/ tempered protective glass	9	
1x250W halogenură metalică/ metal halide	30171010	min. 0.92	460	450	450	sticlă și grătar/ tempered protective glass & grid	9	

PDVM 09

Tip/Type	Cod produs/ Product code	Factor de putere/ Power factor	Dimensiuni/Dimensions [mm]			Accesorii/ Accessories	Masa/ Weight [kg]	Lampa/ Lamp
			φ	H	φ I			
1x250W mercur/mercury	30171003	min. 0.92	460	450	450	-	9	
1x250W mercur/mercury	30171005	min. 0.92	460	450	450	grătar/grid	9	